

# TECHNICAL DATASHEET

## PVX Multimount®

### Description

Multifunctional **wind certified** mounting system for installing mesh tray and / or pipe on flat roofs. Top: mesh tray insertion area with possibility for 3 x wire mesh clip (s). Side: 2 x tube entry  $\varnothing$  16-32 mm + 2 x tube lockers on the top. Lid function for inserting tube. Coupling function for infinite width mounting of mesh tray.



### Technical specifications

- Dimensions (mm): L 150 x W 115 x H 100
- Weight: 1120 gr
- Material: ASA, HDPE, Halogen free
- Maximum load: 50 KG
- Uv protected: 100%
- Temperature: - 40°C to + 60°C
- BallasT Block: Frost resistant concrete, Komo certificated
- Verticale mounting: 2 x M6 mounting holes in bottom including rosette

### Certification

Wind, in accordance with NEN-EN 1881-1-4: 2011, NEN 7250: 2014, CUR Recommendation 103: 2005.

Max wind force: 10 (24,5-28,4 m/s)

### Article number

PVX23011945

### Product warranty

15 year



**PVX Multimount**  
THE NEW STANDARD IN CABLE MANAGEMENT

**PVX Multimount®**

Buitenbaan 70, NL-4206 VT Gorinchem, +31 (0)6-40235633

info@pvxmultimount.com | www.pvxmultimount.com